

AIRMAN®

PORTABLE
SCREW COMPRESSOR
PDS400S/SC
PDSF330DP/DPC
Series



Made in **JAPAN**

Features and Benefits

Reliable performance

5×6 new rotor profile delivers superior performance in severe environment and improves overall reliability.

Pursuit of efficiency

More than 10% of fuel efficiency improvement is achieved comparing to previous model by optimized components.

Availability for wide application

After cooler model is line up to suit a wide range of applications such as pneumatic tools drilling and blasting.

Dual pressure model (PDSF330DP/DPC) can meet different requirements from customers.



HOKUETSU INDUSTRIES CO., LTD.

SPECIFICATIONS

Model	PDS400S -6B5	PDS400SC -6B5 After-Cooler	PDSF330DP -6B5	PDSF330DPC -6B5 After-Cooler
-------	-----------------	----------------------------------	-------------------	------------------------------------

COMPRESSOR

Type	Rotary Twin Screw, Single-Stage, Oil-cooled			
Free Air Delivery m ³ /min	11.3		9.3 / 10.7	
Rated Operating Pressure kg/cm ² (PSIG)(kPa)	7.1 (102)(700)		10.5 (150)(1,030) / 7.1 (102)(700)	
Receiver Tank Capacity m ³ (US gal)	0.077 (20.3)			
Air Outlets	50A×1pcs, 20A×2pcs			

ENGINE

Maker/Model	KUBOTA V3800DI-TI-E2B-COHE1			
Type	4 cycle, water cooled, direct injection type, inter-cooler, turbocharger			
Total Displacement cc	3,769			
No.of Cylinders	4			
Rated Output PS(kW)/rpm	102 (75.2) / 2,600			
Fuel Tank Capacity Liters (US gal)	178 (47.0)			
Lubrication Oil Capacity Liters (US gal)	15.6 (4.1)			

DIMENSION & WEIGHT

Overall Length mm (inch)	3,665 (144.3)			
Overall Width mm (inch)	1,975 (77.8)			
Overall Height mm (inch)	1,750 (68.9)			
Dry Weight kg (lb)	1,740 (3,836)	1,780 (3,924)	1,740 (3,836)	1,780 (3,924)
Wet Weight kg (lb)	1,940 (4,277)	1,980 (4,365)	1,940 (4,277)	1,980 (4,365)
Tire Size	6.50-14 8PR×2W			
Designated Emissions Regulation	JPN Tier2			

● Specifications are subject to change without notice

HOKUETSU INDUSTRIES CO., LTD.

8th Floor Shinjuku San-Ei Bldg.,
22-2 Nishi-Shinjuku 1-Chome, Shinjuku-ku, Tokyo 160-0023 Japan
Tel: 81-3-3348-7281 Fax: 81-3-3348-7289
E-mail: airman_oversea@airman.co.jp
http://www.airman.co.jp

AIRMAN ASIA SDN.BHD.

Suite A-8-2, level8, Block A, Sky Park @ One City,
Jalan USJ 25/1, 47650 Subang Jaya, Selangor, Malaysia
Tel: 60-3-5036-7228 Fax: 60-3-5036-7226
E-mail: sales@airman-asia.com

HOKUETSU INDUSTRIES EUROPE B.V.

Aalsmeerderdijk 156, 1438 AX Oude Meer, Netherland
Tel: 31-20-6462636 Fax: 31-20-6462191
E-mail: info@hokuetsu.nl

AIRMAN USA CORPORATION

7633 Adairsville Hwy Adairsville, GA 30103
Tel: 1-770-769-4241 Fax: 1-770-769-4335
E-mail: info@airman-usa.com



ISO 9001 : JQA-0581
ISO 14001 : JQA-EM4670

SAFETY

- Operate safely in accordance with proper operation manual.
- To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.